

Product information

Special Bulldog Oil SAE 30

PI 14/02/08/2016



Description

Special Bulldog Oil is manufactured using a modified process. This refined product is especially suitable for lubrication in two-stroke internal combustion power engines with hot bulb and total-loss lubrication.

Properties

- mineral based
- unblended
- outstanding lubrication reliability
- low pour point
- guarantees optimum combustion
- low flash point
- prevents oil smuts

Technical data

ISO viscosity class	VG 100 DIN 51519
Density at 15 °C	0,885 g/cm ³ DIN 51757
Viscosity at 40 °C	100 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11,0 mm ² /s ASTM D 7042-04
Viscosity index	94 DIN ISO 2909
Pour point	-18 °C DIN ISO 3016
Flash point	256 °C DIN ISO 2592
Oxide ash	<0,01 g/100g DIN EN ISO 6245
Increase in coke residues	0,9 % DIN 51352 Blatt 1
Initial boiling point	410 °C ASTM D-1160
Color number (ASTM)	L3,0 DIN ISO 2049

Areas of application

Specially developed for Lanz bulldog two-stroke engines with hot bulb and total-loss lubrication. Not suitable for four-stroke engines requiring blended oils or oils with additives.

Application

The operating instructions of the machine manufacturers must be followed.



Available pack sizes

10 l Canister plastic	1400
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.