



**GENERAL FEATURERS**

- Max pressure 40 bar (580 PSI)
- Flowrate 5÷100 l/min (1,3÷26 GPM)
- Parts in contact with fluid made of Teflon® and S.S. AISI316
- Gaskets in Viton®
- Power supply 10÷16 VDC, max absorption 300 mA
- Pulses 600 psi/l (2271 pls/GAL)
- Connection with a 3-poles AMP Superseal® connector
- Output only by flowing fluid; operating status LED

 <b>ARAG</b> <sup>®</sup> A Nordson Company	DISEGNO <b>46211A30000</b>	INDICE MODIFICA <b>0</b>	CLASSE TOLLERANZA EN-ISO 2768-vL PRIMA EMISSIONE DISEGNO
	DENOMINAZIONE <b>FLUSS. EL. ORION2 5/100LT FL463</b>		FIRMA <b>Bassi L.</b>
			DATA <b>01/03/2024</b>
			SCALA <b>1:1.5</b> DIS. <b>A3</b>

QUESTO E' UN DOCUMENTO RISERVATO DI PROPRIETA' DI ARAG srl, via Palladio 5/A 42048 RUBIERA (RE) ITALY. IL SUO CONTENUTO NON POTRA' ESSERE COMUNICATO A TERZI SENZA IL PERMESSO SCRITTO DEL PROPRIETARIO.  
 THIS CONFIDENTIAL DOCUMENT IS EXCLUSIVE PROPERTY OF ARAG srl, via Palladio 5/A 42048 RUBIERA (RE) ITALY. ITS CONTENTS CANNOT BE DISCLOSED TO ANYONE WITHOUT WRITTEN PERMISSION OF THE OWNER.

REV.01